



ITIS BV
Columbusweg 64
NL-4462 HB Goes
T +31 113568515
info@itis-nl.com
www.itis-nl.com

Test certificate:
202000490-C001



Industrie Service

API 607 FIRE TEST QUALIFICATION CERTIFICATE

This certificate is to certify that the valve below has been tested in accordance with, and meets the requirements for operability, through seat leakage and external leakage stated in API Standard 607, seventh edition, June 2016 'Fire Test for Quarter-turn Valves and Valves Equipped with Nonmetallic Seats'.

Test valve details

Manufacturer : Comeval Valve Systems, S.L. y CIA
Address : Carrer les Rotés, 15, 46540 El Puig de Santa Maria, Valencia, Spain
Brand : UNIFLOW
Nominal size : DN100
Pressure rating : Class 150
Flow direction : Bi-directional
Type : Floating Ball valve
Weight : 53.5kg
Bore : Full bore
Drawing number : FLANGED_STAINLESS_CARBON_STEEL_FLOATING_BALL_VALVES-BV4M-UNIFLOW-GENERAL_DRAWING-EN-GD05 date:23-11-2020
Body material : F304 / CF8M
Ball material : CF8
Seat material : PTFE
Stem material : F304
Body gasket material : 304 + Graphite
Stem seal material : 3x Graphite
Identification number : 11K0058A

According to API standard 607, the specified range for covering other sizes/pressure classes is:

Tested valve	Scope of Size	Scope of pressure rating
NPS 4 Class 150	NPS 4; 5; 6; 8 DN 100, 125; 150; 200	Class 150; 300

Disclaimer: Under no circumstances ITIS B.V. can be held responsible applying the above mentioned covering range

This certificate refers to the above mentioned test valve. This certificate does not imply assessment of the production of the valves. This certificate is only valid in conjunction with the full ITIS BV test report number 202000490-R001.

Approved signatory

☒ TESTED
☐ REVIEW
☐ WITNESSED
Date/Signature

J. van der Hoeft

12-01-2021

Name Authority (TUV SUD)

I. van Remoortere

12-01-2021