



ITIS BV
Columbusweg 64
NL-4462 HB Goes
T +31 113568515
info@itis-nl.com
www.itis-nl.com

Test certificate:
202300125-C001



API 607 FIRE TEST QUALIFICATION CERTIFICATE

This certificate is to certify that the valve below has been tested in accordance with, and meets the requirements for operability, through seat leakage and external leakage stated in API Standard 607, eighth edition, October 2022 'Fire Test for Quarter-turn Valves and Valves Equipped with Nonmetallic Seats'.

Test valve details

Manufacturer : COMEVAL VALVE SYSTEMS S.L. y CIA
Address : Les Rotes 15, 46540 El Puig, Valencia (ES)
Brand : UNIFLOW
Nominal size : DN50 (2")
Pressure rating : Class 800
Flow direction : Bi-directional
Valve type : Ball valve
Weight : 40kg
Bore : Full bore
Drawing number + revision : Ball_valve_dn50_class800-uniflow-b8-general_drawing-en rev230323
Body material : ASTM A105
Body/bonnet gaskets : SS304+Graphite
Seat material : PTFE
Stem seal material : Graphite
Stud / Nut material : ASTM A193 B7 / ASTM A194 2H
Identification number : 17-00007-03
Gearbox : N/A

According to API standard 607, the specified range for covering other sizes/pressure classes is:

Tested valve	Scope of Size	Scope of pressure rating
NPS 2	NPS 2 and below; 2 1/2; 3; 4	Class 800; 900; 1500
Class 800	DN 50 and below; 65; 80; 100	

Disclaimer: Under no circumstances ITIS B.V. can be held responsible applying the above mentioned covering range

This certificate is issued under the provision that the Raad voor Accreditatie does not assume any liability and refers to the above mentioned test valve. This certificate does not imply assessment of the production of the valves and is only valid in conjunction with the full ITIS BV test report number 202300125-R001.

Approved signatory

J. VAN DER HOFF

J. van der Hoeff

17-04-2023